

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

We Claim

1. A method for detecting head motion and providing feedback to a user engaged in a physical activity the method comprising:

5 providing head gear for wearing on a user's head, wherein the head gear
 comprises a sensor for detecting motion of the head gear;
 providing a processor that
 stores a predetermined sensor value corresponding to a preferred path
 of motion for the head gear and
10 receives input from the sensor indicative of the motion of the head
 gear;
 comparing the input from the sensor to the predetermined sensor value; and
 generating a feedback signal indicating the result of the comparison of the
 input from the sensor to the predetermined sensor value.

- 15 2. The method of claim 1, wherein the physical activity comprises hitting a golf ball and
 the step of comparing the input from the sensor to the predetermined sensor value
 further comprises:

20 comparing the input from the sensor to a stored sensor value indicating that the
 head gear has remained in an arming position for a predetermined
 duration.

3. The method of claim 2, wherein the step of generating a feedback signal further
comprises:

25 generating an arming feedback signal when the result of the step of comparing
 the input from the sensor to a stored sensor value indicates that the
 input substantially agrees with the stored sensor value.

- 30 4. The method of claim 1, wherein the physical activity comprises hitting a golf ball and
 the step of comparing the input from the sensor to the predetermined sensor value
 further comprises:

comparing the input from the sensor to a stored sensor value indicating a
backswing head position.

5. The method of claim 4, wherein the step of generating a feedback signal further
comprises:

generating a first backswing feedback signal when the result of the step of
comparing the input from the sensor to the stored sensor value
indicates that the head gear rotated beyond a predetermined rotation
point;

generating a second backswing feedback signal when the result of the step of
comparing the input from the sensor to the stored sensor value
indicates that the head gear translated beyond a predetermined
translation point; and

generating a third backswing feedback signal when the result of the step of
comparing the input from the sensor to the stored sensor value
indicates that the head gear inclined or declined beyond a
predetermined inclination point.

6. The method of claim 1, wherein the physical activity comprises hitting a golf ball and
the step of comparing the input from the sensor to the predetermined sensor value
further comprises:

comparing the input from the sensor to a stored sensor value indicating a
forward swing head position.

7. The method of claim 6, wherein the step of generating a feedback signal further
comprises:

generating a first forward swing feedback signal when the result of the step of
comparing the input from the sensor to the stored sensor value
indicates that the head gear rotated beyond a predetermined rotation
point;

generating a second forward swing feedback signal when the result of the step
of comparing the input from the sensor to the stored sensor value
indicates that the head gear translated beyond a predetermined
translation point; and

5 generating a third forward swing feedback signal when the result of the step of
comparing the input from the sensor to the stored sensor value
indicates that the head gear inclined or declined beyond a
predetermined inclination point.

10 8. The method of claim 1, wherein the physical activity comprises hitting a golf ball and
the step of comparing the input from the sensor to the predetermined sensor value
further comprises:

comparing the input from the sensor to a stored sensor value indicating a
follow through head position.

15 9. The method of claim 8, wherein the step of generating a feedback signal further
comprises:

generating a first follow through feedback signal when the result of the step of
comparing the input from the sensor to the stored sensor value
20 indicates that the head gear rotated beyond a predetermined rotation
point;

generating a second follow through feedback signal when the result of the step
of comparing the input from the sensor to the stored sensor value
indicates that the head gear translated beyond a predetermined
25 translation point; and

generating a third follow through feedback signal when the result of the step of
comparing the input from the sensor to the stored sensor value
indicates that the head gear inclined or declined beyond a
predetermined inclination point.

10. The method of claim 1, wherein the physical activity comprises hitting a ball with a bat and the step of comparing the input from the sensor to the predetermined sensor value further comprises:

5 comparing the input from the sensor to a stored sensor value indicating that the head gear has remained in an arming position for a predetermined duration.

11. The method of claim 10, wherein the step of generating a feedback signal further comprises:

10 generating a first arming feedback signal when the result of the step of comparing the input from the sensor to a stored sensor value indicates that the input substantially agrees with the stored sensor value; and
 generating a second arming feedback signal when the result of the step of comparing the input from the sensor to a stored sensor value indicates
15 that the input does not substantially agree with the stored sensor value.

12. The method of claim 1, wherein the physical activity comprises hitting a ball with a bat and the step of comparing the input from the sensor to the predetermined sensor value further comprises:

20 comparing the input from the sensor to a stored sensor value indicating a load at pitch head position.

13. The method of claim 12, wherein the step of generating a feedback signal further comprises:

25 generating a load at pitch feedback signal when the result of the step of comparing the input from the sensor to a stored sensor value indicates that the input deviates from the stored sensor value.

14. The method of claim 1, wherein the physical activity comprises hitting a ball with a bat and the step of comparing the input from the sensor to the predetermined sensor value further comprises:
- 30

comparing the input from the sensor to a stored sensor value indicating bat swing head position.

15. The method of claim 15, wherein the step of generating a feedback signal further comprises:

generating a feedback signal when the result of the step of comparing the input from the sensor to a stored sensor value indicates that the input deviates from the stored sensor value.

16. The method of claim 1, wherein the physical activity comprises hitting a ball with a bat and the step of comparing the input from the sensor to the predetermined sensor value further comprises:

comparing the input from the sensor to a stored sensor value indicating follow through head position.

17. The method of claim 16, wherein the step of generating a feedback signal further comprises:

generating a feedback signal when the result of the step of comparing the input from the sensor to a stored sensor value indicates that the input deviates from the stored sensor value.

18. An apparatus for detecting the motion of a user's head during the user's performance of a physical activity, the apparatus comprising:

a sensor, wearable on the user's head, wherein the sensor detects motion of the user's head;

a processor that

stores a predetermined sensor value corresponding to a preferred path of motion for the head gear,

receives input from the sensor indicative of the motion of the head gear, and

compares the input from the sensor to the stored sensor value; and

a feedback indicator that generates a feedback signal indicative of the result of the comparison of the input from the sensor to the stored sensor value.

19. The apparatus of claim 18, wherein the sensor further comprises:

5 a band, wearable about the user's head, and comprising three sensor nodes positioned around the band.

20. The apparatus of claim 19, wherein the three sensor nodes are positioned around the band at positions along a circumference of the band that substantially correspond to
10 locations of 90 degrees, 180 degrees, and 270 degrees.

21. The apparatus of claim 18, wherein the sensor comprises a gyroscopic sensor.

22. The apparatus of claim 18, wherein the sensor comprises an accelerometer sensor.

23. The apparatus of claim 18, wherein the processor further comprises:

15 a data augmentation unit comprising a portable processor based device.

24. The apparatus of claim 23, wherein the data augmentation unit further comprises:

20 an interface that enables data stored in the data augmentation device to be uploaded to a processor based device.

25. The apparatus of claim 24, wherein the processor based device further comprises:

25 a processor based device capable of communicating over the Internet.

26. The apparatus of claim 18, wherein the feedback indicator further comprises:

a display on a data augmentation unit.

27. The apparatus of claim 26, wherein the display further comprises:

30 a screen for displaying visually perceptible information.

28. The apparatus of claim 23, wherein the data augmentation unit further comprises:
a user interface to enable the user to input information.

5 29. The apparatus of claim 28, wherein the input information further comprises:
information relating to a club type.

30. The apparatus of claim 28, wherein the input information further comprises:
information relating to a distance from a target.

10 31. The apparatus of claim 28, wherein the input information further comprises:
information relating to an angle from a target.

32. The apparatus of claim 28, wherein the input information further comprises:
information relating to scorekeeping.

15 33. The apparatus of claim 28, wherein the input information further comprises:
information relating to a pitch type.

20 34. The apparatus of claim 28, wherein the input information further comprises:
information relating to a pitch speed.

35. The apparatus of claim 28, wherein the input information further comprises:
information relating to a pitch location.

25 36. The apparatus of claim 28, wherein the input information further comprises:
information relating to a hit result.

37. The apparatus of claim 28, wherein the input information further comprises:
information relating to a field position.

30 38. The apparatus of claim 28, wherein the input information further comprises:

information relating to a batting average.

39. The apparatus of claim 23, wherein the data augmentation unit receives input from the sensor via a wireless connection.

- 5
40. A method for providing analysis of a physical activity comprising:
enabling a user to upload data pertaining to the user's head motion during the
physical activity onto a processor based device;
enabling an evaluator to access the data pertaining to the user's head motion;
10 and
communicating, to the user, the evaluator's analysis of the data pertaining to
the user's head motion.

41. The method of claim 40, further comprising:
15 collecting the data pertaining to the user's head motion using a head motion
sensing apparatus.

42. The method of claim 40, wherein the step of enabling a user to upload data further
comprises:
20 enabling the user to upload data to a processor based device that is connected
to a network of processor based devices.

43. The method of claim 42, wherein the network of processor based devices further
comprises the Internet.

- 25
44. The method of claim 40, wherein the step of enabling an evaluator to access the data
further comprises:
enabling the evaluator to access the data pertaining to the user's head motion
via a network of processor based devices.
30

45. The method of claim 44, wherein the network of processor based devices further comprises the Internet.

46. The method of claim 40, wherein the step of communicating the evaluator's analysis further comprises:

communicating the evaluator's analysis via a network of processor based devices.

47. The method of claim 46, wherein the network of processor based devices further comprises the Internet.

48. The method of claim 40, wherein the physical activity is golf.

49. The method of claim 40, wherein the physical activity is batting.

50. A data collection unit capable of receiving a signal from an input device and storing the signals in a digital format, the data collection unit comprising:

an input channel for receiving input from a sensor;

a set point sensor for sensing a set point event that indicates a transition in a data collection process;

a data storage device for storing data corresponding to the input received at the input channel;

an interface for uploading the stored data to a processor device.

51. The data collection unit of claim 50, further comprising:
a remote display.

52. The data collection unit of claim 50, wherein the set point sensor further comprises:
a microphone for sensing an audible set point event.

53. The data collection unit of claim 50, wherein the sensor further comprises:
- a gyroscopic sensor;
 - a accelerometer sensor; and
 - a housing that houses the gyroscopic sensor and the accelerometer sensor.

5